

Testing machine



Pro Series







The CTM model hydraulic press, which is part of the HOYTOM PRO series, can achieve nominal capacities of up to 6000 kN. This equipment has been especially designed to test the compressive strength of cylindrical, cubic and prismatic concrete test specimens, and to test for indirect traction, in compliance with the corresponding standards.

Each machine includes Hoytom's HoyWin® test control software, and our custom designed electronics. This enables users to extract maximum performance and accuracy, through a simple and intuitive interface.

Typical applications are aimed at the construction industry, where it is used for testing materials such as concrete, rocks and cement.

Characteristics:



- Extremely rigid frame for minimum deformation during testing.
- Top plate with ball joint.
- Computer, HoyWin® software and monitor (peripherals).
- Side guard.
- Modern appearance with ergonomic design.
- Easy to transport via forklift or crane.

Capacity kN	2000 - 3000	4500	6000
Maximum Speed		50	
Piston travel		75	
Piston diameter	350	430	470
Adjustment N/s		0-10000 (via PC)	
Drive		Electro-Hydraulic	
Plate dimensions	Top plate Ø 320	Top plate Ø 320	Top plate Ø 320
	Bottom plate Ø 410	Bottom plate Ø 510	Bottom plate Ø 520
Distance between plates		320	
Distance between columns	480	530	580
Working height	800	800	950
Dimensions (W x D x H)	1200 x 500 x 1650	1250 x 550 x 1650	1300 x 700 x 1750
Weight Kg	1550	2550	2700
Power supply		380-III	

Pressure transducer		
Machine accuracy (Class) *1	1	
Range	5% - 100% FS	
Resolution	0.01% FS	

^{*1} According to Standards ISO 7500 and ASTM E4.

















Moytom@hoytom.com